L&L Luce&Light

Made in Italy

Strip LED Slim, code: BASSTSLI2000195
Linear profiles for indoor applications

CE UKCA LED TECH IP20 A↑G F ▷

DESCRIPTION

linear profile for indoor applications; recessed, surface mounted (ceiling, wall, floor); Power consumption: 8W; Power supply: 24Vdc; Delivered lumen output: 800 lm/m; 140 mid-power LEDs; LED colour: 4000K; CRI Colour Rendering Index: 95; power supply unit not included; Ingress protection: IP20; Dimensions: 5000 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WDA00 Profile - Micro, WDA05 Profile - Corner, WDA05N Profile - Corner, WDA05Z Profile - Corner, WDA06 Profile - Corner, WDA07 Profile - Line Plus, WDA08 Profile - Line Plus, WDA09 Profile - Plaster Plus, WDA10 Profile - Plaster Plus, WDA12 Profile - Lyna, WDA13 Profile - Lyna, WEA00 End cap - Micro, WEA01 End cap with hole - Micro, WEA05 End cap - Corner, WEA06 End cap with hole - Corner, WEA07 End cap - Line Plus, WEA08 End cap with hole - Line Plus, WEA09 End cap with hole - Plaster Plus, WEA10 End cap - Lyna, WR0000S0M Cover - Micro, WR0000S0S Cover - Micro, WR0000S0T Cover - Micro, WR0000S1M Cover - Line / Line Plus / Plaster / Plaster Plus / Corner, WR0000S1S Cover - Line / Line Plus / Plaster / Plaster Plus / Corner, WR0000S1T Cover - Line / Line Plus / Plaster / Plaster Plus / Corner, WR0000S2M Cover - Line / Line Plus / Plaster / Plaster Plus / Corner, WR0000S2S Cover - Line / Line Plus / Plaster / Plaster Plus / Corner, WR0000S2T Cover - Line / Line Plus / Plaster / Plaster Plus / Corner, WR0000S3S Cover - Lyna, WR0000S4M Cover - Lyna, WR0000S4S Cover - Lyna, WR0000S5M Cover - Lyna; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Product being discontinued

L&L Luce&Light srl / via Trescalini, 5 / 36031 Dueville, Vicenza / Italy
T +39 0444 36 05 71 / E lucelight@lucelight.it / www.lucelight.it

1/6

ELECTRICAL CHARACTERISTICS

Power consumption	8W
Power supply	24Vdc
Power supply unit	power supply unit not included

LIGHTING CHARACTERISTICS

Number and type of LED	140 mid-power LEDs
LED colour	4000K
CRI Colour Rendering Index	95
Delivered lumen output	800 lm/m

MECHANICAL CHARACTERISTICS

Dimensions	5000 mm

GENERAL CHARACTERISTICS

Ingress protection	IP20
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Walkover	no
Drive-over	no

L&L Luce&Light srl / via Trescalini, 5 / 36031 Dueville, Vicenza / Italy
T +39 0444 36 05 71 / E lucelight@lucelight.it / www.lucelight.it

2/6

PHOTOMETRIC DATA

SLIM – 100cm FROST

Lux max (3000K)   cd/Klm max 340   — C0 - C180

H (m)	Ø (m)	
0.50	1.55	755
1.00	3.09	189
1.50	4.64	84
2.00	6.18	47
2.50	7.73	30
3.00	9.27	21

30°   30°

0°

ACCESSORIES

Optical Accessories

WR0000S0M
Cover - Micro
milky - 2000 mm

WR0000S0S
Cover - Micro
frosted - 2000 mm

WR0000S0T
Cover - Micro
transparent - 2000 mm

WR0000S1M
Cover - Line / Line Plus / Plaster / Plaster Plus / Corner
milky - 2000 mm

WR0000S1S
Cover - Line / Line Plus / Plaster / Plaster Plus / Corner
frosted - 2000 mm

WR0000S1T
Cover - Line / Line Plus / Plaster / Plaster Plus / Corner
transparent - 2000 mm

WR0000S2M

WR0000S2S

L&L Luce&Light srl / via Trescalini, 5 / 36031 Dueville, Vicenza / Italy
T +39 0444 36 05 71 / E lucelight@lucelight.it / www.lucelight.it

3/6

Cover - Line / Line Plus / Plaster / Plaster Plus / Corner
milky - 3000 mm

Cover - Line / Line Plus / Plaster / Plaster Plus / Corner
frosted - 3000 mm

WR0000S2T
Cover - Line / Line Plus / Plaster / Plaster Plus / Corner
transparent - 3000 mm

WR0000S3S
Cover - Lyna
frosted - 2000 mm

WR0000S4S
Cover - Lyna
frosted - 1000 mm

WR0000S4M
Cover - Lyna
milky - 1000 mm

WR0000S5M
Cover - Lyna
milky - 2000 mm

Other

WDA00
Profile - Micro
aluminium - 2000 mm

WDA05
Profile - Corner
aluminium - 2000 mm

WDA05N
Profile - Corner
aluminium - 2000 mm - black

WDA05Z
Profile - Corner
aluminium - 2000 mm - bronze

L&L Luce&Light srl / via Trescalini, 5 / 36031 Dueville, Vicenza / Italy
T +39 0444 36 05 71 / E lucelight@lucelight.it / www.lucelight.it

4/6

WDA06
Profile - Corner
aluminium - 3000 mm

WDA07
Profile - Line Plus
aluminium - 2000 mm

WDA08
Profile - Line Plus
aluminium - 3000 mm

WDA09
Profile - Plaster Plus
aluminium - 2000 mm

WDA10
Profile - Plaster Plus
aluminium - 3000 mm

WDA12
Profile - Lyna
aluminium - 1000 mm

WDA13
Profile - Lyna
aluminium - 2000 mm

WEA00
End cap - Micro
grey - 1 piece

WEA01
End cap with hole - Micro
grey - 1 piece

WEA05
End cap - Corner
grey - 1 piece

L&L Luce&Light srl / via Trescalini, 5 / 36031 Dueville, Vicenza / Italy
T +39 0444 36 05 71 / E lucelight@lucelight.it / www.lucelight.it

5/6

WEA06
End cap with hole - Corner
grey - 1 piece

WEA07
End cap - Line Plus
grey - 1 piece

WEA08
End cap with hole - Line Plus
grey - 1 piece

WEA09
End cap with hole - Plaster Plus
grey - 1 piece

WEA10
End cap - Lyna
grey - 1 piece

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.

L&L Luce&Light srl / via Trescalini, 5 / 36031 Dueville, Vicenza / Italy
T +39 0444 36 05 71 / E lucelight@lucelight.it / www.lucelight.it

6/6