










Made in Italy

 Versa 2.0, code: VR20105DB  
Wall mounted for indoor applications

21/11/2024 Rev. 34





 kg 0,40
 




## DESCRIPTION

wall mounted for indoor applications, double beam; surface mounted (wall); Power consumption: 18W; Power supply: 230Vac; Lumen output at source: 1646 lm (3000K); Delivered lumen output: 1170 lm (3000K); mid-power LED matrix, 3-step MacAdam, 50 000h L80 B10 (Ta 25°C); LED colour: 3000K; Optics: diffuse; CRI Colour Rendering Index: 80; Body material: body in steel; Finishes: white (RAL 9003); RAL finish on request; Screen material: screen in one-side-frosted, transparent plexiglass; built-in power supply unit; terminal block; Ingress protection: IP40; Casambi-compatible version, controllable with the Casambi app, available on request; Design by: arch. Enrico Novello; Operating temperature: 0°C — +45°C; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class I; Weight: 400 g; Dimensions: 120x120x80 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

### ELECTRICAL CHARACTERISTICS

Power consumption	18W
Power supply	230Vac
Power supply unit	built-in power supply unit

### LIGHTING CHARACTERISTICS

Number and type of LED	mid-power LED matrix
Average LED life	50 000h L80 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	80
Binning	3-step MacAdam
Optics	diffuse
Lumen output at source	1646 lm (3000K)
Delivered lumen output	1170 lm (3000K)

### MECHANICAL CHARACTERISTICS


Dimensions	120x120x80 mm
Weight	400 g
Finishes	white RAL 9003
Mounting	surface mounted (wall)
Body material	body in steel
Screen material	screen in one-side-frosted, transparent plexiglass

### GENERAL CHARACTERISTICS


Ingress protection	IP40
Operating temperature	0°C — +45°C
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Appliance class	class I
Walkover	no
Drive-over	no
Power cables	terminal block
Photobiological safety	photobiological safety: risk group 1 according to EN 62471:2006
Notes	Casambi-compatible version, controllable with the Casambi app, available on request

PHOTOMETRIC DATA

D - Diffuse, up beam



D - Diffuse, down beam



double-beam

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.