




Made in Italy

 Flori 1.0, code: FS10101FMT
Projectors for outdoor applications

18/07/2024 Rev. 26



DESCRIPTION

projector for outdoor applications; surface mounted (ceiling, wall, ground, spike, strap); Power consumption: 7W; Power supply: 230Vac; Lumen output at source: 608 lm (3000K, CRI >90); Delivered lumen output: 296 lm (3000K, 31°, CRI >90); 1 power LED High Intensity, 3-step MacAdam, 50 000h L90 B10 (Ta 25°C); LED colour: 2700K; Optics: 31°; CRI Colour Rendering Index: >90; Body material: body in aluminium; Finishes: cor-ten; RAL finish on request; Screen material: screen in serigraphed, transparent and tempered extra-clear glass; built-in power supply unit; includes 1.5 m neoprene cable H05RN-F 3x1,0 Ø7 mm; Ingress protection: IP66; Impact resistance: IK07; version with 24Vdc power supply available on request, Casambi-compatible version, controllable with the Casambi app, available on request; Protection systems: IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit; The PID (Protective Impedance Device) protects lighting fixtures from electrical phenomena external to the system, such as static electricity accumulation or electromagnetic interference coming from the mains power. Generally, these are events with a low energy content; Operating temperature: -20°C — +45°C; Glow wire test: 960°; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class I; Weight: 800 g; Dimensions: Ø60x154x147 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WB1001T Standard snoot - cor-ten, WB1002T Asymmetrical snoot - cor-ten, WB1003N Barn doors - black, WHA0005 Honeycomb louvre , WP0100 Spike for in-ground installation, WP1001T Spike with bracket for in-ground installation - h 500 mm - cor-ten, WP1002T Spike with bracket for in-ground installation - h 800 mm - cor-ten, WP1003T Arm with bracket for wall-mounted installation - h 420 mm - cor-ten, WP1004 Fastener strap - 5 m; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

ELECTRICAL CHARACTERISTICS

Power consumption	7W
Power supply	230Vac
Power supply unit	built-in power supply unit

LIGHTING CHARACTERISTICS

Number and type of LED	1 power LED High Intensity
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	2700K
CRI Colour Rendering Index	>90
Binning	3-step MacAdam
Optics	31°
Lumen output at source	608 lm (3000K, CRI >90)
Delivered lumen output	296 lm (3000K, 31°, CRI >90)

MECHANICAL CHARACTERISTICS


Dimensions	Ø60x154x147 mm
Weight	800 g
Finishes	cor-ten
Mounting	with bracket, screws and plugs
Body material	body in aluminium
Screen material	screen in serigraphed, transparent, tempered extra-clear glass

GENERAL CHARACTERISTICS

Ingress protection	IP66
Operating temperature	-20°C — +45°C
Impact resistance	IK07
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°
Appliance class	class I
Walkover	no
Drive-over	no
Power cables	includes 1.5 m neoprene cable H05RN-F 3x1,0 Ø7 mm
Protection systems	IPS (Intelligent Protection System); PID (Protective Impedance Device)
Photobiological safety	photobiological safety: risk group 1 according to EN 62471:2006
Notes	version with 24Vdc power supply available on request, Casambi-compatible version, controllable with the Casambi app, available on request

PHOTOMETRIC DATA

M - 31° CRI 80




ACCESSORIES


Installation Accessories



WP0100
Spike for in-ground installation



WP1001T
Spike with bracket for in-ground installation - h 500 mm - cor-ten



WP1002T
Spike with bracket for in-ground installation - h 800 mm - cor-ten



WP1003T
Arm with bracket for wall-mounted installation - h 420 mm - cor-ten

Anti-glare




WB1001T
Standard snoot - cor-ten



WB1002T
Asymmetrical snoot - cor-ten



WB1003N



WHA0005

Barn doors - black

Honeycomb louvre
built into the lighting fixture

Order together with the lighting fixture

Other



WP1004

Fastener strap - 5 m

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.